

※ **Features:**

- ◆ 1080P 5 in 1 DVR, compatitable with IP, AHD, TVI, CVI, CVBS
- ◆ Free P2P Cloud Service, Plug & Play
- ◆ Full 1080P Recording and Playback
- ◆ Digital Channel support Onvif Protocol
- ◆ Motion Detection with Email Alert
- ◆ Remote View & Control, Anywhere, anytime.
- ◆ Support Andriod Mobile, Tablets, iPhone, iPad.
- ◆ Demenstion: 245mm× 330mm× 55mm
- ◆ Weight: 3.0 KG



※ **Specification:**

Model ID:		
System	Main Processor	Hi3521A
	Operation System	LINUX, Compression Mode: H.264
Video	Video Input	8CH BNC
	Video Output	1 x VGA / 1 x HDMI (1920*1080)
	Video Distance	75-3 Cable up to 500 Meters / Video No Decay and Distortion
Audio	Audio Input	4CH RCA(Add to 8 CH)
	Audio Output	1CH RCA
Recording	Recording Channel	8CH × 1080P;1080P: 1920 x 1080 at 15 Fps(NTSC), 15 Fps(PAL) (5 in 1) 8CH × 4M: 4M at 15 Fps(NTSC), 15 Fps(PAL) (AHD) 8CH × 3M: 3M at 18 Fps(NTSC), 18 Fps(PAL)(AHD)
	Reolution	1080P: 1920 × 1080 3M:2560 ×1440 4M:2688 ×1520
	Recording Mode	Realtime Video Recording
Playback	Playback Channel	8CH x 1080P 15 Fps/8CH x 4M at 8Fps/8CH x 3M at 10Fps
	Playback Mode	Normal Play, Fast Forward, Frame by Frame, Zoom In / Out
	Search Mode	Time, Date, Motion Detection, Exact Search
Alarm	Alarm Input	N/A
	Alarm Output	N/A
Storage	HDD Interface	1 x SATA Fixed HDD
	Capability	SATA HDD up to 6TB each
Backup	USB Disk	2 x USB 2.0 port
	Backup Format	H.264 (only for Playback Software - General H.264 Player V1.7.0.)
	Backup Mode	Network download / Flash USB / movable HDD/SATA HDD / DVD-RW
PTZ	PTZ	R485 control
Network	Interface	RJ45 port / 10M / 100M / 1,000Mbps Ethernet
	Protocol	TCP/IP, DHCP, DDNS, PPPoE, UPNP, NTP, SMTP, FTP, RTSP, ARSP,3G,WiFi
	Mobile phone Support	mobile view app Smart meye (iPhone, Android)
	Computer System Support	Windows 2000, XP, Vista, 7, 8 / Mac OS x 10.6/10.7
	Compatible Browser	iCloud Software, one-click online; Support IE, Firefox, Google Chrome
	Free DDNS	iCloud Free DDNS Server (P2P function)
	IP Camera Protocol	ONVIF Version Platform Protocol (Digital Menu)
Others	Simultaneous Remote Viewers	6 Users Online
	Operating Temperature	0°C ~ 55°C
	Operating Humidity	10% ~ 90%
	Dimension	245mm× 330mm× 55mm
	Weight	3.0 KG
	HDD Screw	4 PCS (1 Pack)
	Accessories	USB Mouse ×1PC/User Manual ×1PC/ Power Supply × 1PC/ Client software CD ×1PC
	Power Supply	DC12V/3A Power Adapter